

**NAME**

xcb\_convert\_selection -

**SYNOPSIS**

```
#include <xcb/xproto.h>
```

**Request function**

```
xcb_void_cookie_t xcb_convert_selection(xcb_connection_t *conn, xcb_window_t requestor,  
    xcb_atom_t selection, xcb_atom_t target, xcb_atom_t property, xcb_timestamp_t time);
```

**REQUEST ARGUMENTS**

<i>conn</i>	The XCB connection to X11.
<i>requestor</i>	TODO: NOT YET DOCUMENTED.
<i>selection</i>	TODO: NOT YET DOCUMENTED.
<i>target</i>	TODO: NOT YET DOCUMENTED.
<i>property</i>	TODO: NOT YET DOCUMENTED.
<i>time</i>	TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_convert\_selection\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from xproto.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.