

NAME

xcb_copy_plane -

SYNOPSIS

```
#include <xcb/xproto.h>
```

Request function

```
xcb_void_cookie_t xcb_copy_plane(xcb_connection_t *conn, xcb_drawable_t src_drawable,  
    xcb_drawable_t dst_drawable, xcb_gcontext_t gc, int16_t src_x, int16_t src_y, int16_t dst_x,  
    int16_t dst_y, uint16_t width, uint16_t height, uint32_t bit_plane);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>src_drawable</i>	TODO: NOT YET DOCUMENTED.
<i>dst_drawable</i>	TODO: NOT YET DOCUMENTED.
<i>gc</i>	TODO: NOT YET DOCUMENTED.
<i>src_x</i>	TODO: NOT YET DOCUMENTED.
<i>src_y</i>	TODO: NOT YET DOCUMENTED.
<i>dst_x</i>	TODO: NOT YET DOCUMENTED.
<i>dst_y</i>	TODO: NOT YET DOCUMENTED.
<i>width</i>	TODO: NOT YET DOCUMENTED.
<i>height</i>	TODO: NOT YET DOCUMENTED.
<i>bit_plane</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_copy_plane_checked*.

See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from xproto.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.