

NAME

xcb_dri2_get_param -

SYNOPSIS

```
#include <xcb/dri2.h>
```

Request function

```
xcb_dri2_get_param_cookie_t xcb_dri2_get_param(xcb_connection_t *conn,
        xcb_drawable_t drawable, uint32_t param);
```

Reply datastructure

```
typedef struct xcb_dri2_get_param_reply_t {
    uint8_t response_type;
    uint8_t is_param_recognized;
    uint16_t sequence;
    uint32_t length;
    uint32_t value_hi;
    uint32_t value_lo;
} xcb_dri2_get_param_reply_t;
```

Reply function

```
xcb_dri2_get_param_reply_t *xcb_dri2_get_param_reply(xcb_connection_t *conn,
        xcb_dri2_get_param_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>drawable</i>	TODO: NOT YET DOCUMENTED.
<i>param</i>	TODO: NOT YET DOCUMENTED.

REPLY FIELDS

<i>response_type</i>	The type of this reply, in this case <i>XCB_DRI2_GET_PARAM</i> . This field is also present in the <i>xcb_generic_reply_t</i> and can be used to tell replies apart from each other.
<i>sequence</i>	The sequence number of the last request processed by the X11 server.
<i>length</i>	The length of the reply, in words (a word is 4 bytes).

is_param_recognized

TODO: NOT YET DOCUMENTED.

value_hi

TODO: NOT YET DOCUMENTED.

value_lo

TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_dri2_get_param_cookie_t*. Errors have to be handled when calling the reply function *xcb_dri2_get_param_reply*.

If you want to handle errors in the event loop instead, use *xcb_dri2_get_param_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from dri2.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.