

NAME

xcb_dri3_open -

SYNOPSIS

```
#include <xcb/dri3.h>
```

Request function

```
xcb_dri3_open_cookie_t xcb_dri3_open(xcb_connection_t *conn, xcb_drawable_t drawable,  
uint32_t provider);
```

Reply datastructure

```
typedef struct xcb_dri3_open_reply_t {  
    uint8_t response_type;  
    uint8_t nfd;  
    uint16_t sequence;  
    uint32_t length;  
    uint8_t pad0[24];  
} xcb_dri3_open_reply_t;
```

Reply function

```
xcb_dri3_open_reply_t *xcb_dri3_open_reply(xcb_connection_t *conn,  
xcb_dri3_open_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

drawable TODO: NOT YET DOCUMENTED.

provider TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_DRI3_OPEN*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

nfd TODO: NOT YET DOCUMENTED.

device_fd TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_dri3_open_cookie_t*. Errors have to be handled when calling the reply function *xcb_dri3_open_reply*.

If you want to handle errors in the event loop instead, use *xcb_dri3_open_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from dri3.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.