

NAME

xcb_dri3_pixmap_from_buffer -

SYNOPSIS

```
#include <xcb/dri3.h>
```

Request function

```
xcb_void_cookie_t xcb_dri3_pixmap_from_buffer(xcb_connection_t *conn, xcb_pixmap_t pixmap,  
xcb_drawable_t drawable, uint32_t size, uint16_t width, uint16_t height, uint16_t stride,  
uint8_t depth, uint8_t bpp, int32_t pixmap_fd);
```

REQUEST ARGUMENTS

| | |
|------------------|----------------------------|
| <i>conn</i> | The XCB connection to X11. |
| <i>pixmap</i> | TODO: NOT YET DOCUMENTED. |
| <i>drawable</i> | TODO: NOT YET DOCUMENTED. |
| <i>size</i> | TODO: NOT YET DOCUMENTED. |
| <i>width</i> | TODO: NOT YET DOCUMENTED. |
| <i>height</i> | TODO: NOT YET DOCUMENTED. |
| <i>stride</i> | TODO: NOT YET DOCUMENTED. |
| <i>depth</i> | TODO: NOT YET DOCUMENTED. |
| <i>bpp</i> | TODO: NOT YET DOCUMENTED. |
| <i>pixmap_fd</i> | TODO: NOT YET DOCUMENTED. |

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_dri3_pixmap_from_buffer_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from dri3.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.