

NAME

xcb_glx_get_booleanv -

SYNOPSIS

```
#include <xcb/glx.h>
```

Request function

```
xcb_glx_get_booleanv_cookie_t xcb_glx_get_booleanv(xcb_connection_t *conn,
    xcb_glx_context_tag_t context_tag, int32_t pname);
```

Reply datastructure

```
typedef struct xcb_glx_get_booleanv_reply_t {
    uint8_t response_type;
    uint8_t pad0;
    uint16_t sequence;
    uint32_t length;
    uint8_t pad1[4];
    uint32_t n;
    uint8_t datum;
    uint8_t pad2[15];
} xcb_glx_get_booleanv_reply_t;
```

Reply function

```
xcb_glx_get_booleanv_reply_t *xcb_glx_get_booleanv_reply(xcb_connection_t *conn,
    xcb_glx_get_booleanv_cookie_t cookie, xcb_generic_error_t **e);
```

Reply accessors

```
uint8_t *xcb_glx_get_booleanv_data(const xcb_glx_get_booleanv_request_t *reply);
```

```
int xcb_glx_get_booleanv_data_length(const xcb_glx_get_booleanv_reply_t *reply);
```

```
xcb_generic_iterator_t xcb_glx_get_booleanv_data_end(const xcb_glx_get_booleanv_reply_t *reply);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

context_tag TODO: NOT YET DOCUMENTED.

pname TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_GLX_GET_BOOLEANV*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

n TODO: NOT YET DOCUMENTED.

datum TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_glx_get_booleanv_cookie_t*. Errors have to be handled when calling the reply function *xcb_glx_get_booleanv_reply*.

If you want to handle errors in the event loop instead, use *xcb_glx_get_booleanv_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from glx.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.