

xcb_glx_get_compressed_tex_image_arb(3) XCB Requests xcb_glx_get_compressed_tex_image_arb(3)

NAME

xcb_glx_get_compressed_tex_image_arb -

SYNOPSIS

```
#include <xcb/glx.h>
```

Request function

```
xcb_glx_get_compressed_tex_image_arb_cookie_t  
xcb_glx_get_compressed_tex_image_arb(xcb_connection_t *conn,  
xcb_glx_context_tag_t context_tag, uint32_t target, int32_t level);
```

Reply datastructure

```
typedef struct xcb_glx_get_compressed_tex_image_arb_reply_t {  
    uint8_t response_type;  
    uint8_t pad0;  
    uint16_t sequence;  
    uint32_t length;  
    uint8_t pad1[8];  
    int32_t size;  
    uint8_t pad2[12];  
} xcb_glx_get_compressed_tex_image_arb_reply_t;
```

Reply function

```
xcb_glx_get_compressed_tex_image_arb_reply_t  
*xcb_glx_get_compressed_tex_image_arb_reply(xcb_connection_t *conn,  
xcb_glx_get_compressed_tex_image_arb_cookie_t cookie, xcb_generic_error_t **e);
```

Reply accessors

```
uint8_t *xcb_glx_get_compressed_tex_image_arb_data(const  
xcb_glx_get_compressed_tex_image_arb_request_t *reply);
```

```
int xcb_glx_get_compressed_tex_image_arb_data_length(const  
xcb_glx_get_compressed_tex_image_arb_reply_t *reply);
```

```
xcb_generic_iterator_t xcb_glx_get_compressed_tex_image_arb_data_end(const  
xcb_glx_get_compressed_tex_image_arb_reply_t *reply);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

xcb_glx_get_compressed_tex_image_arb(3) XCB Requests xcb_glx_get_compressed_tex_image_arb(3)

context_tag TODO: NOT YET DOCUMENTED.

target TODO: NOT YET DOCUMENTED.

level TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case `XCB_GLX_GET_COMPRESSED_TEX_IMAGE_ARB`. This field is also present in the `xcb_generic_reply_t` and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

size TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an `xcb_glx_get_compressed_tex_image_arb_cookie_t`. Errors have to be handled when calling the reply function `xcb_glx_get_compressed_tex_image_arb_reply`.

If you want to handle errors in the event loop instead, use `xcb_glx_get_compressed_tex_image_arb_unchecked`. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from `glx.xml`. Contact `xcb@lists.freedesktop.org` for corrections and improvements.