NAME

xcb_glx_get_minmax -

SYNOPSIS

#include <xcb/glx.h>

Request function

xcb_glx_get_minmax_cookie_t **xcb_glx_get_minmax**(xcb_connection_t *_conn_,
xcb_glx_context_tag_t _context_tag_, uint32_t _target_, uint32_t _format_, uint32_t _type_,
uint8_t _swap_bytes_, uint8_t _reset_);

Reply datastructure

```
typedef struct xcb_glx_get_minmax_reply_t {
   uint8_t  response_type;
   uint8_t  pad0;
   uint16_t sequence;
   uint32_t length;
   uint8_t  pad1[24];
} xcb_glx_get_minmax_reply_t;
```

Reply function

xcb_glx_get_minmax_reply_t ***xcb_glx_get_minmax_reply**(xcb_connection_t *_conn_,
xcb_glx_get_minmax_cookie_t _cookie_, xcb_generic_error_t ***_e_);

Reply accessors

uint8_t ***xcb_glx_get_minmax_data**(const xcb_glx_get_minmax_request_t *_reply_);

int **xcb_glx_get_minmax_data_length**(const xcb_glx_get_minmax_reply_t *_reply_);

xcb_generic_iterator_t **xcb_glx_get_minmax_data_end**(const xcb_glx_get_minmax_reply_t *_reply_);

REQUEST ARGUMENTS

conn The XCB connection to X11.

_context_tag_ TODO: NOT YET DOCUMENTED.

target TODO: NOT YET DOCUMENTED.

format TODO: NOT YET DOCUMENTED.

type TODO: NOT YET DOCUMENTED.

swap_bytes TODO: NOT YET DOCUMENTED.

reset TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_GLX_GET_MINMAX*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

DESCRIPTION

RETURN VALUE

Returns an *xcb_glx_get_minmax_cookie_t*. Errors have to be handled when calling the reply function *xcb_glx_get_minmax_reply*.

If you want to handle errors in the event loop instead, use *xcb_glx_get_minmax_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from glx.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.