

NAME

xcb_glx_set_client_info_arb -

SYNOPSIS

```
#include <xcb/glx.h>
```

Request function

```
xcb_void_cookie_t xcb_glx_set_client_info_arb(xcb_connection_t *conn, uint32_t major_version,  
uint32_t minor_version, uint32_t num_versions, uint32_t gl_str_len, uint32_t glx_str_len, const  
uint32_t *gl_versions, const char *gl_extension_string, const char *glx_extension_string);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

major_version TODO: NOT YET DOCUMENTED.

minor_version TODO: NOT YET DOCUMENTED.

num_versions TODO: NOT YET DOCUMENTED.

gl_str_len TODO: NOT YET DOCUMENTED.

glx_str_len TODO: NOT YET DOCUMENTED.

gl_versions TODO: NOT YET DOCUMENTED.

gl_extension_string
 TODO: NOT YET DOCUMENTED.

glx_extension_string
 TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_glx_set_client_info_arb_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from glx.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.