

NAME

xcb_glx_use_x_font -

SYNOPSIS

```
#include <xcb/glx.h>
```

Request function

```
xcb_void_cookie_t xcb_glx_use_x_font(xcb_connection_t *conn, xcb_glx_context_tag_t context_tag,  
xcb_font_t font, uint32_t first, uint32_t count, uint32_t list_base);
```

REQUEST ARGUMENTS

| | |
|--------------------|----------------------------|
| <i>conn</i> | The XCB connection to X11. |
| <i>context_tag</i> | TODO: NOT YET DOCUMENTED. |
| <i>font</i> | TODO: NOT YET DOCUMENTED. |
| <i>first</i> | TODO: NOT YET DOCUMENTED. |
| <i>count</i> | TODO: NOT YET DOCUMENTED. |
| <i>list_base</i> | TODO: NOT YET DOCUMENTED. |

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_glx_use_x_font_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from glx.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.