

xcb_input_change_device_key_mapping(3) XCB Requests xcb_input_change_device_key_mapping(3)

NAME

xcb_input_change_device_key_mapping -

SYNOPSIS

```
#include <xcb/xinput.h>
```

Request function

```
xcb_void_cookie_t xcb_input_change_device_key_mapping(xcb_connection_t *conn,  
    uint8_t device_id, xcb_input_key_code_t first_keycode, uint8_t keysyms_per_keycode,  
    uint8_t keycode_count, const xcb_keysym_t *keysyms);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

device_id TODO: NOT YET DOCUMENTED.

first_keycode TODO: NOT YET DOCUMENTED.

keysyms_per_keycode
 TODO: NOT YET DOCUMENTED.

keycode_count TODO: NOT YET DOCUMENTED.

keysyms TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_input_change_device_key_mapping_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xinput.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.