

xcb\_input\_change\_device\_notify\_event\_t(3) XCB Events xcb\_input\_change\_device\_notify\_event\_t(3)

## NAME

xcb\_input\_change\_device\_notify\_event\_t -

## SYNOPSIS

```
#include <xcb/xinput.h>
```

### Event datastructure

```
typedef struct xcb_input_change_device_notify_event_t {
    uint8_t    response_type;
    uint8_t    device_id;
    uint16_t   sequence;
    xcb_timestamp_t time;
    uint8_t    request;
    uint8_t    pad0[23];
} xcb_input_change_device_notify_event_t;
```

## EVENT FIELDS

*response\_type* The type of this event, in this case *XCB\_INPUT\_CHANGE\_DEVICE\_NOTIFY*. This field is also present in the *xcb\_generic\_event\_t* and can be used to tell events apart from each other.

*sequence* The sequence number of the last request processed by the X11 server.

*device\_id* NOT YET DOCUMENTED.

*time* NOT YET DOCUMENTED.

*request* NOT YET DOCUMENTED.

## DESCRIPTION

### SEE ALSO

### AUTHOR

Generated from xinput.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.