

**NAME**

xcb\_input\_device\_focus\_in\_event\_t -

**SYNOPSIS**

```
#include <xcb/xinput.h>
```

**Event datastructure**

```
typedef struct xcb_input_device_focus_in_event_t {
    uint8_t    response_type;
    uint8_t    detail;
    uint16_t   sequence;
    xcb_timestamp_t time;
    xcb_window_t window;
    uint8_t    mode;
    uint8_t    device_id;
    uint8_t    pad0[18];
} xcb_input_device_focus_in_event_t;
```

**EVENT FIELDS**

*response\_type* The type of this event, in this case *XCB\_INPUT\_DEVICE\_FOCUS\_OUT*. This field is also present in the *xcb\_generic\_event\_t* and can be used to tell events apart from each other.

*sequence* The sequence number of the last request processed by the X11 server.

*detail* NOT YET DOCUMENTED.

*time* NOT YET DOCUMENTED.

*window* NOT YET DOCUMENTED.

*mode* NOT YET DOCUMENTED.

*device\_id* NOT YET DOCUMENTED.

**DESCRIPTION****SEE ALSO****AUTHOR**

Generated from xinput.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.