

NAME

xcb_input_property_event_t -

SYNOPSIS

```
#include <xcb/xinput.h>
```

Event datastructure

```
typedef struct xcb_input_property_event_t {
    uint8_t      response_type;
    uint8_t      extension;
    uint16_t     sequence;
    uint32_t     length;
    uint16_t     event_type;
    xcb_input_device_id_t deviceid;
    xcb_timestamp_t time;
    xcb_atom_t   property;
    uint8_t      what;
    uint8_t      pad0[11];
    uint32_t     full_sequence;
} xcb_input_property_event_t;
```

EVENT FIELDS

response_type The type of this event, in this case *XCB_INPUT_PROPERTY*. This field is also present in the *xcb_generic_event_t* and can be used to tell events apart from each other.

sequence The sequence number of the last request processed by the X11 server.

extension NOT YET DOCUMENTED.

length NOT YET DOCUMENTED.

event_type NOT YET DOCUMENTED.

deviceid NOT YET DOCUMENTED.

time NOT YET DOCUMENTED.

property NOT YET DOCUMENTED.

what NOT YET DOCUMENTED.

full_sequence NOT YET DOCUMENTED.

DESCRIPTION**SEE ALSO****AUTHOR**

Generated from xinput.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.