

NAME

xcb_input_raw_button_press_event_t -

SYNOPSIS

```
#include <xcb/xinput.h>
```

Event datastructure

```
typedef struct xcb_input_raw_button_press_event_t {
    uint8_t      response_type;
    uint8_t      extension;
    uint16_t     sequence;
    uint32_t     length;
    uint16_t     event_type;
    xcb_input_device_id_t deviceid;
    xcb_timestamp_t time;
    uint32_t     detail;
    xcb_input_device_id_t sourceid;
    uint16_t     valuators_len;
    uint32_t     flags;
    uint8_t      pad0[4];
    uint32_t     full_sequence;
} xcb_input_raw_button_press_event_t;
```

EVENT FIELDS

response_type The type of this event, in this case *XCB_INPUT_RAW_MOTION*. This field is also present in the *xcb_generic_event_t* and can be used to tell events apart from each other.

sequence The sequence number of the last request processed by the X11 server.

extension NOT YET DOCUMENTED.

length NOT YET DOCUMENTED.

event_type NOT YET DOCUMENTED.

deviceid NOT YET DOCUMENTED.

time NOT YET DOCUMENTED.

xcb_input_raw_button_press_event_t(3) XCB Events xcb_input_raw_button_press_event_t(3)

detail NOT YET DOCUMENTED.

sourceid NOT YET DOCUMENTED.

valuators_len NOT YET DOCUMENTED.

flags NOT YET DOCUMENTED.

full_sequence NOT YET DOCUMENTED.

DESCRIPTION

SEE ALSO

AUTHOR

Generated from xinput.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.