

**NAME**

xcb\_input\_set\_device\_focus -

**SYNOPSIS**

```
#include <xcb/xinput.h>
```

**Request function**

```
xcb_void_cookie_t xcb_input_set_device_focus(xcb_connection_t *conn, xcb_window_t focus,  
      xcb_timestamp_t time, uint8_t revert_to, uint8_t device_id);
```

**REQUEST ARGUMENTS**

<i>conn</i>	The XCB connection to X11.
<i>focus</i>	TODO: NOT YET DOCUMENTED.
<i>time</i>	TODO: NOT YET DOCUMENTED.
<i>revert_to</i>	TODO: NOT YET DOCUMENTED.
<i>device_id</i>	TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_input\_set\_device\_focus\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from xinput.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.