NAME
>   xcb_input_set_device_modifier_mapping -

SYNOPSIS
>   **#include <xcb/xinput.h>**

 Request function
>   xcb_input_set_device_modifier_mapping_cookie_t
>   **xcb_input_set_device_modifier_mapping**(xcb_connection_t *_conn_, uint8_t _device_id_,
>   uint8_t _keycodes_per_modifier_, const uint8_t *_keymaps_);

 Reply datastructure

>   typedef struct xcb_input_set_device_modifier_mapping_reply_t {
>   uint8_t _response_type_;
>   uint8_t _xi_reply_type_;
>   uint16_t _sequence_;
>   uint32_t _length_;
>   uint8_t _status_;
>   uint8_t _pad0_[23];
>   } **xcb_input_set_device_modifier_mapping_reply_t**;

 Reply function
>   xcb_input_set_device_modifier_mapping_reply_t
>   ***xcb_input_set_device_modifier_mapping_reply**(xcb_connection_t *_conn_,
>   xcb_input_set_device_modifier_mapping_cookie_t _cookie_, xcb_generic_error_t **_e_);

REQUEST ARGUMENTS
>   _conn_   The XCB connection to X11.

>   _device_id_   TODO: NOT YET DOCUMENTED.

>   _keycodes_per_modifier_
>   TODO: NOT YET DOCUMENTED.

>   _keymaps_   TODO: NOT YET DOCUMENTED.

REPLY FIELDS
>   _response_type_ The type of this reply, in this case
>   _XCB_INPUT_SET_DEVICE_MODIFIER_MAPPING_. This field is also present in

the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence   The sequence number of the last request processed by the X11 server.

length   The length of the reply, in words (a word is 4 bytes).

xi_reply_type   TODO: NOT YET DOCUMENTED.

status   TODO: NOT YET DOCUMENTED.

DESCRIPTION
RETURN VALUE
Returns an *xcb_input_set_device_modifier_mapping_cookie_t*. Errors have to be handled when calling the reply function *xcb_input_set_device_modifier_mapping_reply*.

If you want to handle errors in the event loop instead, use *xcb_input_set_device_modifier_mapping_unchecked*. See **xcb-requests(3)** for details.

ERRORS
This request does never generate any errors.

SEE ALSO
AUTHOR
Generated from xinput.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.