

**NAME**

xcb\_input\_ungrab\_device\_key -

**SYNOPSIS**

```
#include <xcb/xinput.h>
```

**Request function**

```
xcb_void_cookie_t xcb_input_ungrab_device_key(xcb_connection_t *conn,  
        xcb_window_t grabWindow, uint16_t modifiers, uint8_t modifier_device, uint8_t key,  
        uint8_t grabbed_device);
```

**REQUEST ARGUMENTS**

*conn*            The XCB connection to X11.

*grabWindow*    TODO: NOT YET DOCUMENTED.

*modifiers*      TODO: NOT YET DOCUMENTED.

*modifier\_device*  
                  TODO: NOT YET DOCUMENTED.

*key*            TODO: NOT YET DOCUMENTED.

*grabbed\_device*  
                  TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_input\_ungrab\_device\_key\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from xinput.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.