

NAME

xcb_randr_change_output_property -

SYNOPSIS

```
#include <xcb/randr.h>
```

Request function

```
xcb_void_cookie_t xcb_randr_change_output_property(xcb_connection_t *conn,  
    xcb_randr_output_t output, xcb_atom_t property, xcb_atom_t type, uint8_t format, uint8_t mode,  
    uint32_t num_units, const void *data);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>output</i>	TODO: NOT YET DOCUMENTED.
<i>property</i>	TODO: NOT YET DOCUMENTED.
<i>type</i>	TODO: NOT YET DOCUMENTED.
<i>format</i>	TODO: NOT YET DOCUMENTED.
<i>mode</i>	TODO: NOT YET DOCUMENTED.
<i>num_units</i>	TODO: NOT YET DOCUMENTED.
<i>data</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_randr_change_output_property_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

xcb_randr_change_output_property(3)

XCB Requests

xcb_randr_change_output_property(3)

Generated from randr.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.