

**NAME**

xcb\_randr\_get\_provider\_property -

**SYNOPSIS**

```
#include <xcb/randr.h>
```

**Request function**

```
xcb_randr_get_provider_property_cookie_t  
xcb_randr_get_provider_property(xcb_connection_t *conn, xcb_randr_provider_t provider,  
xcb_atom_t property, xcb_atom_t type, uint32_t long_offset, uint32_t long_length, uint8_t _delete,  
uint8_t pending);
```

**Reply datastructure**

```
typedef struct xcb_randr_get_provider_property_reply_t {  
    uint8_t response_type;  
    uint8_t format;  
    uint16_t sequence;  
    uint32_t length;  
    xcb_atom_t type;  
    uint32_t bytes_after;  
    uint32_t num_items;  
    uint8_t pad0[12];  
} xcb_randr_get_provider_property_reply_t;
```

**Reply function**

```
xcb_randr_get_provider_property_reply_t  
*xcb_randr_get_provider_property_reply(xcb_connection_t *conn,  
xcb_randr_get_provider_property_cookie_t cookie, xcb_generic_error_t **e);
```

**Reply accessors**

```
void *xcb_randr_get_provider_property_data(const xcb_randr_get_provider_property_request_t  
*reply);
```

```
int xcb_randr_get_provider_property_data_length(const xcb_randr_get_provider_property_reply_t  
*reply);
```

```
xcb_generic_iterator_t xcb_randr_get_provider_property_data_end(const  
xcb_randr_get_provider_property_reply_t *reply);
```

**REQUEST ARGUMENTS**

<i>conn</i>	The XCB connection to X11.
<i>provider</i>	TODO: NOT YET DOCUMENTED.
<i>property</i>	TODO: NOT YET DOCUMENTED.
<i>type</i>	TODO: NOT YET DOCUMENTED.
<i>long_offset</i>	TODO: NOT YET DOCUMENTED.
<i>long_length</i>	TODO: NOT YET DOCUMENTED.
<i>_delete</i>	TODO: NOT YET DOCUMENTED.
<i>pending</i>	TODO: NOT YET DOCUMENTED.

**REPLY FIELDS**

<i>response_type</i>	The type of this reply, in this case <i>XCB_RANDR_GET_PROVIDER_PROPERTY</i> . This field is also present in the <i>xcb_generic_reply_t</i> and can be used to tell replies apart from each other.
<i>sequence</i>	The sequence number of the last request processed by the X11 server.
<i>length</i>	The length of the reply, in words (a word is 4 bytes).
<i>format</i>	TODO: NOT YET DOCUMENTED.
<i>type</i>	TODO: NOT YET DOCUMENTED.
<i>bytes_after</i>	TODO: NOT YET DOCUMENTED.
<i>num_items</i>	TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_randr\_get\_provider\_property\_cookie\_t*. Errors have to be handled when calling the reply function *xcb\_randr\_get\_provider\_property\_reply*.

If you want to handle errors in the event loop instead, use

*xcb\_randr\_get\_provider\_property\_unchecked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from randr.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.