

**NAME**

xcb\_randr\_set\_panning -

**SYNOPSIS**

```
#include <xcb/randr.h>
```

**Request function**

```
xcb_randr_set_panning_cookie_t xcb_randr_set_panning(xcb_connection_t *conn,  
    xcb_randr_crtc_t crtc, xcb_timestamp_t timestamp, uint16_t left, uint16_t top, uint16_t width,  
    uint16_t height, uint16_t track_left, uint16_t track_top, uint16_t track_width,  
    uint16_t track_height, int16_t border_left, int16_t border_top, int16_t border_right,  
    int16_t border_bottom);
```

**Reply datastructure**

```
typedef struct xcb_randr_set_panning_reply_t {  
    uint8_t    response_type;  
    uint8_t    status;  
    uint16_t   sequence;  
    uint32_t   length;  
    xcb_timestamp_t timestamp;  
} xcb_randr_set_panning_reply_t;
```

**Reply function**

```
xcb_randr_set_panning_reply_t *xcb_randr_set_panning_reply(xcb_connection_t *conn,  
    xcb_randr_set_panning_cookie_t cookie, xcb_generic_error_t **e);
```

**REQUEST ARGUMENTS**

<i>conn</i>	The XCB connection to X11.
<i>crtc</i>	TODO: NOT YET DOCUMENTED.
<i>timestamp</i>	TODO: NOT YET DOCUMENTED.
<i>left</i>	TODO: NOT YET DOCUMENTED.
<i>top</i>	TODO: NOT YET DOCUMENTED.
<i>width</i>	TODO: NOT YET DOCUMENTED.

<i>height</i>	TODO: NOT YET DOCUMENTED.
<i>track_left</i>	TODO: NOT YET DOCUMENTED.
<i>track_top</i>	TODO: NOT YET DOCUMENTED.
<i>track_width</i>	TODO: NOT YET DOCUMENTED.
<i>track_height</i>	TODO: NOT YET DOCUMENTED.
<i>border_left</i>	TODO: NOT YET DOCUMENTED.
<i>border_top</i>	TODO: NOT YET DOCUMENTED.
<i>border_right</i>	TODO: NOT YET DOCUMENTED.
<i>border_bottom</i>	TODO: NOT YET DOCUMENTED.

## REPLY FIELDS

<i>response_type</i>	The type of this reply, in this case <i>XCB_RANDR_SET_PANNING</i> . This field is also present in the <i>xcb_generic_reply_t</i> and can be used to tell replies apart from each other.
<i>sequence</i>	The sequence number of the last request processed by the X11 server.
<i>length</i>	The length of the reply, in words (a word is 4 bytes).
<i>status</i>	TODO: NOT YET DOCUMENTED.
<i>timestamp</i>	TODO: NOT YET DOCUMENTED.

## DESCRIPTION

### RETURN VALUE

Returns an *xcb\_randr\_set\_panning\_cookie\_t*. Errors have to be handled when calling the reply function *xcb\_randr\_set\_panning\_reply*.

If you want to handle errors in the event loop instead, use *xcb\_randr\_set\_panning\_unchecked*. See **xcb-requests(3)** for details.

## ERRORS

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from randr.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.