

## NAME

xcb\_randr\_set\_provider\_offload\_sink -

## SYNOPSIS

```
#include <xcb/randr.h>
```

### Request function

```
xcb_void_cookie_t xcb_randr_set_provider_offload_sink(xcb_connection_t *conn,  
    xcb_randr_provider_t provider, xcb_randr_provider_t sink_provider,  
    xcb_timestamp_t config_timestamp);
```

## REQUEST ARGUMENTS

*conn*           The XCB connection to X11.

*provider*       TODO: NOT YET DOCUMENTED.

*sink\_provider*   TODO: NOT YET DOCUMENTED.

*config\_timestamp*  
                  TODO: NOT YET DOCUMENTED.

## DESCRIPTION

### RETURN VALUE

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_randr\_set\_provider\_offload\_sink\_checked*. See **xcb-requests(3)** for details.

## ERRORS

This request does never generate any errors.

## SEE ALSO

### AUTHOR

Generated from randr.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.