

**NAME**

xcb\_render\_add\_glyphs -

**SYNOPSIS**

```
#include <xcb/render.h>
```

**Request function**

```
xcb_void_cookie_t xcb_render_add_glyphs(xcb_connection_t *conn, xcb_render_glyphset_t glyphset,  
uint32_t glyphs_len, const uint32_t *glyphids, const xcb_render_glyphinfo_t *glyphs,  
uint32_t data_len, const uint8_t *data);
```

**REQUEST ARGUMENTS**

<i>conn</i>	The XCB connection to X11.
<i>glyphset</i>	TODO: NOT YET DOCUMENTED.
<i>glyphs_len</i>	TODO: NOT YET DOCUMENTED.
<i>glyphids</i>	TODO: NOT YET DOCUMENTED.
<i>glyphs</i>	TODO: NOT YET DOCUMENTED.
<i>data_len</i>	TODO: NOT YET DOCUMENTED.
<i>data</i>	TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_render\_add\_glyphs\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from render.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.