

**NAME**

xcb\_render\_create\_picture -

**SYNOPSIS**

```
#include <xcb/render.h>
```

**Request function**

```
xcb_void_cookie_t xcb_render_create_picture(xcb_connection_t *conn, xcb_render_picture_t pid,  
      xcb_drawable_t drawable, xcb_render_pictformat_t format, uint32_t value_mask, const  
      void *value_list);
```

**REQUEST ARGUMENTS**

<i>conn</i>	The XCB connection to X11.
<i>pid</i>	TODO: NOT YET DOCUMENTED.
<i>drawable</i>	TODO: NOT YET DOCUMENTED.
<i>format</i>	TODO: NOT YET DOCUMENTED.
<i>value_mask</i>	TODO: NOT YET DOCUMENTED.
<i>value_list</i>	TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_render\_create\_picture\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from render.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.