

NAME

xcb_render_create_picture -

SYNOPSIS

```
#include <xcb/render.h>
```

Request function

```
xcb_void_cookie_t xcb_render_create_picture(xcb_connection_t *conn, xcb_render_picture_t pid,  
      xcb_drawable_t drawable, xcb_render_pictformat_t format, uint32_t value_mask, const  
      void *value_list);
```

REQUEST ARGUMENTS

| | |
|-------------------|----------------------------|
| <i>conn</i> | The XCB connection to X11. |
| <i>pid</i> | TODO: NOT YET DOCUMENTED. |
| <i>drawable</i> | TODO: NOT YET DOCUMENTED. |
| <i>format</i> | TODO: NOT YET DOCUMENTED. |
| <i>value_mask</i> | TODO: NOT YET DOCUMENTED. |
| <i>value_list</i> | TODO: NOT YET DOCUMENTED. |

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_render_create_picture_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from render.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.