

NAME

xcb_render_fill_rectangles -

SYNOPSIS

```
#include <xcb/render.h>
```

Request function

```
xcb_void_cookie_t xcb_render_fill_rectangles(xcb_connection_t *conn, uint8_t op,  
xcb_render_picture_t dst, xcb_render_color_t color, uint32_t rects_len, const  
xcb_rectangle_t *rects);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>op</i>	TODO: NOT YET DOCUMENTED.
<i>dst</i>	TODO: NOT YET DOCUMENTED.
<i>color</i>	TODO: NOT YET DOCUMENTED.
<i>rects_len</i>	TODO: NOT YET DOCUMENTED.
<i>rects</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_render_fill_rectangles_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from render.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.