

xcb_render_query_pict_index_values(3) XCB Requests xcb_render_query_pict_index_values(3)

NAME

xcb_render_query_pict_index_values -

SYNOPSIS

```
#include <xcb/render.h>
```

Request function

```
xcb_render_query_pict_index_values_cookie_t  
xcb_render_query_pict_index_values(xcb_connection_t *conn, xcb_render_pictformat_t format);
```

Reply datastructure

```
typedef struct xcb_render_query_pict_index_values_reply_t {  
    uint8_t response_type;  
    uint8_t pad0;  
    uint16_t sequence;  
    uint32_t length;  
    uint32_t num_values;  
    uint8_t pad1[20];  
} xcb_render_query_pict_index_values_reply_t;
```

Reply function

```
xcb_render_query_pict_index_values_reply_t  
*xcb_render_query_pict_index_values_reply(xcb_connection_t *conn,  
                                         xcb_render_query_pict_index_values_cookie_t cookie, xcb_generic_error_t **e);
```

Reply accessors

```
xcb_render_indexvalue_t *xcb_render_query_pict_index_values_values(const  
                     xcb_render_query_pict_index_values_request_t *reply);
```

```
int xcb_render_query_pict_index_values_length(const  
                     xcb_render_query_pict_index_values_reply_t *reply);
```

```
xcb_render_indexvalue_iterator_t xcb_render_query_pict_index_values_values_iterator(const  
                     xcb_render_query_pict_index_values_reply_t *reply);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

format TODO: NOT YET DOCUMENTED.

REPLY FIELDS

- response_type* The type of this reply, in this case *XCB_RENDER_QUERY_PICT_INDEX_VALUES*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.
- sequence* The sequence number of the last request processed by the X11 server.
- length* The length of the reply, in words (a word is 4 bytes).
- num_values* TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_render_query_pict_index_values_cookie_t*. Errors have to be handled when calling the reply function *xcb_render_query_pict_index_values_reply*.

If you want to handle errors in the event loop instead, use *xcb_render_query_pict_index_values_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from render.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.