

NAME

xcb_shape_input_selected -

SYNOPSIS

```
#include <xcb/shape.h>
```

Request function

```
xcb_shape_input_selected_cookie_t xcb_shape_input_selected(xcb_connection_t *conn,
    xcb_window_t destination_window);
```

Reply datastructure

```
typedef struct xcb_shape_input_selected_reply_t {
    uint8_t response_type;
    uint8_t enabled;
    uint16_t sequence;
    uint32_t length;
} xcb_shape_input_selected_reply_t;
```

Reply function

```
xcb_shape_input_selected_reply_t *xcb_shape_input_selected_reply(xcb_connection_t *conn,
    xcb_shape_input_selected_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

destination_window
 TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_SHAPE_INPUT_SELECTED*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

enabled TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_shape_input_selected_cookie_t*. Errors have to be handled when calling the reply function *xcb_shape_input_selected_reply*.

If you want to handle errors in the event loop instead, use *xcb_shape_input_selected_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from shape.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.