

**NAME**

xcb\_shape\_mask -

**SYNOPSIS**

```
#include <xcb/shape.h>
```

**Request function**

```
xcb_void_cookie_t xcb_shape_mask(xcb_connection_t *conn, xcb_shape_op_t operation,  
    xcb_shape_kind_t destination_kind, xcb_window_t destination_window, int16_t x_offset,  
    int16_t y_offset, xcb_pixmap_t source_bitmap);
```

**REQUEST ARGUMENTS**

*conn*            The XCB connection to X11.

*operation*        TODO: NOT YET DOCUMENTED.

*destination\_kind*  
                  TODO: NOT YET DOCUMENTED.

*destination\_window*  
                  TODO: NOT YET DOCUMENTED.

*x\_offset*         TODO: NOT YET DOCUMENTED.

*y\_offset*         TODO: NOT YET DOCUMENTED.

*source\_bitmap*   TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_shape\_mask\_checked*.  
See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from shape.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.