

NAME

xcb_sync_query_alarm -

SYNOPSIS

```
#include <xcb/sync.h>
```

Request function

```
xcb_sync_query_alarm_cookie_t xcb_sync_query_alarm(xcb_connection_t *conn,
    xcb_sync_alarm_t alarm);
```

Reply datastructure

```
typedef struct xcb_sync_query_alarm_reply_t {
    uint8_t      response_type;
    uint8_t      pad0;
    uint16_t     sequence;
    uint32_t     length;
    xcb_sync_trigger_t trigger;
    xcb_sync_int64_t delta;
    uint8_t      events;
    uint8_t      state;
    uint8_t      pad1[2];
} xcb_sync_query_alarm_reply_t;
```

Reply function

```
xcb_sync_query_alarm_reply_t *xcb_sync_query_alarm_reply(xcb_connection_t *conn,
    xcb_sync_query_alarm_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

alarm TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_SYNC_QUERY_ALARM*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

<i>length</i>	The length of the reply, in words (a word is 4 bytes).
<i>trigger</i>	TODO: NOT YET DOCUMENTED.
<i>delta</i>	TODO: NOT YET DOCUMENTED.
<i>events</i>	TODO: NOT YET DOCUMENTED.
<i>state</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_sync_query_alarm_cookie_t*. Errors have to be handled when calling the reply function *xcb_sync_query_alarm_reply*.

If you want to handle errors in the event loop instead, use *xcb_sync_query_alarm_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from sync.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.