

NAME

xcb_sync_query_fence -

SYNOPSIS

```
#include <xcb/sync.h>
```

Request function

```
xcb_sync_query_fence_cookie_t xcb_sync_query_fence(xcb_connection_t *conn,
    xcb_sync_fence_t fence);
```

Reply datastructure

```
typedef struct xcb_sync_query_fence_reply_t {
    uint8_t response_type;
    uint8_t pad0;
    uint16_t sequence;
    uint32_t length;
    uint8_t triggered;
    uint8_t pad1[23];
} xcb_sync_query_fence_reply_t;
```

Reply function

```
xcb_sync_query_fence_reply_t *xcb_sync_query_fence_reply(xcb_connection_t *conn,
    xcb_sync_query_fence_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

fence TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_SYNC_QUERY_FENCE*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

triggered TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_sync_query_fence_cookie_t*. Errors have to be handled when calling the reply function *xcb_sync_query_fence_reply*.

If you want to handle errors in the event loop instead, use *xcb_sync_query_fence_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from sync.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.