

NAME

xcb_ungrab_button -

SYNOPSIS

```
#include <xcb/xproto.h>
```

Request function

```
xcb_void_cookie_t xcb_ungrab_button(xcb_connection_t *conn, uint8_t button,  
xcb_window_t grab_window, uint16_t modifiers);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

button One of the following values:

XCB_BUTTON_INDEX_ANY

Any of the following (or none):

XCB_BUTTON_INDEX_1

The left mouse button.

XCB_BUTTON_INDEX_2

The right mouse button.

XCB_BUTTON_INDEX_3

The middle mouse button.

XCB_BUTTON_INDEX_4

Scroll wheel. TODO: direction?

XCB_BUTTON_INDEX_5

Scroll wheel. TODO: direction?

TODO: NOT YET DOCUMENTED.

grab_window TODO: NOT YET DOCUMENTED.

modifiers TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_ungrab_button_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xproto.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.