

**NAME**

xcb\_ungrab\_key - release a key combination

**SYNOPSIS**

```
#include <xcb/xproto.h>
```

**Request function**

```
xcb_void_cookie_t xcb_ungrab_key(xcb_connection_t *conn, xcb_keycode_t key,  
                                xcb_window_t grab_window, uint16_t modifiers);
```

**REQUEST ARGUMENTS**

*conn*            The XCB connection to X11.

*key*            The keycode of the specified key combination.

Using the special value *XCB\_GRAB\_ANY* means releasing all possible key codes.

*grab\_window*   The window on which the grabbed key combination will be released.

*modifiers*     The modifiers of the specified key combination.

Using the special value *XCB\_MOD\_MASK\_ANY* means releasing the key combination with every possible modifier combination.

**DESCRIPTION**

Releases the key combination on *grab\_window* if you grabbed it using *xcb\_grab\_key* before.

**RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_ungrab\_key\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

*xcb\_value\_error\_t*

TODO: reasons?

*xcb\_window\_error\_t*

The specified *grab\_window* does not exist.

**SEE ALSO**

**xcb-requests(3)**, **xcb\_grab\_key(3)**, **xev(1)**

**AUTHOR**

Generated from xproto.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.