

NAME

xcb_ungrab_key - release a key combination

SYNOPSIS

```
#include <xcb/xproto.h>
```

Request function

```
xcb_void_cookie_t xcb_ungrab_key(xcb_connection_t *conn, xcb_keycode_t key,  
                                xcb_window_t grab_window, uint16_t modifiers);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

key The keycode of the specified key combination.

Using the special value *XCB_GRAB_ANY* means releasing all possible key codes.

grab_window The window on which the grabbed key combination will be released.

modifiers The modifiers of the specified key combination.

Using the special value *XCB_MOD_MASK_ANY* means releasing the key combination with every possible modifier combination.

DESCRIPTION

Releases the key combination on *grab_window* if you grabbed it using *xcb_grab_key* before.

RETURN VALUE

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_ungrab_key_checked*. See **xcb-requests(3)** for details.

ERRORS

xcb_value_error_t

TODO: reasons?

xcb_window_error_t

The specified *grab_window* does not exist.

SEE ALSO

xcb-requests(3), xcb_grab_key(3), xev(1)

AUTHOR

Generated from xproto.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.