

NAME

xcb_x_print_print_query_screens -

SYNOPSIS

```
#include <xcb/xprint.h>
```

Request function

```
xcb_x_print_print_query_screens_cookie_t xcb_x_print_print_query_screens(xcb_connection_t *conn,
```

Reply datastructure

```
typedef struct xcb_x_print_print_query_screens_reply_t {
    uint8_t response_type;
    uint8_t pad0;
    uint16_t sequence;
    uint32_t length;
    uint32_t listCount;
    uint8_t pad1[20];
} xcb_x_print_print_query_screens_reply_t;
```

Reply function

```
xcb_x_print_print_query_screens_reply_t
*xcb_x_print_print_query_screens_reply(xcb_connection_t *conn,
    xcb_x_print_print_query_screens_cookie_t cookie, xcb_generic_error_t **e);
```

Reply accessors

```
xcb_window_t *xcb_x_print_print_query_screens_roots(const
    xcb_x_print_print_query_screens_request_t *reply);

int xcb_x_print_print_query_screens_roots_length(const xcb_x_print_print_query_screens_reply_t
    *reply);

xcb_generic_iterator_t xcb_x_print_print_query_screens_roots_end(const
    xcb_x_print_print_query_screens_reply_t *reply);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

REPLY FIELDS

response_type The type of this reply, in this case `XCB_X_PRINT_PRINT_QUERY_SCREEN`S. This

field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

listCount TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_x_print_print_query_screens_cookie_t*. Errors have to be handled when calling the reply function *xcb_x_print_print_query_screens_reply*.

If you want to handle errors in the event loop instead, use *xcb_x_print_print_query_screens_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xprint.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.