

**NAME**

xcb\_x\_print\_print\_query\_version -

**SYNOPSIS**

```
#include <xcb/xprint.h>
```

**Request function**

```
xcb_x_print_print_query_version_cookie_t xcb_x_print_print_query_version(xcb_connection_t *conn,
```

**Reply datastructure**

```
typedef struct xcb_x_print_print_query_version_reply_t {
    uint8_t response_type;
    uint8_t pad0;
    uint16_t sequence;
    uint32_t length;
    uint16_t major_version;
    uint16_t minor_version;
} xcb_x_print_print_query_version_reply_t;
```

**Reply function**

```
xcb_x_print_print_query_version_reply_t
*xcb_x_print_print_query_version_reply(xcb_connection_t *conn,
    xcb_x_print_print_query_version_cookie_t cookie, xcb_generic_error_t **e);
```

**REQUEST ARGUMENTS**

*conn*            The XCB connection to X11.

**REPLY FIELDS**

*response\_type*    The type of this reply, in this case *XCB\_X\_PRINT\_PRINT\_QUERY\_VERSION*. This field is also present in the *xcb\_generic\_reply\_t* and can be used to tell replies apart from each other.

*sequence*        The sequence number of the last request processed by the X11 server.

*length*          The length of the reply, in words (a word is 4 bytes).

*major\_version*    TODO: NOT YET DOCUMENTED.

*minor\_version*    TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_x\_print\_print\_query\_version\_cookie\_t*. Errors have to be handled when calling the reply function *xcb\_x\_print\_print\_query\_version\_reply*.

If you want to handle errors in the event loop instead, use *xcb\_x\_print\_print\_query\_version\_unchecked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from xprint.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.