

NAME

xcb_x_print_print_set_attributes -

SYNOPSIS

```
#include <xcb/xprint.h>
```

Request function

```
xcb_void_cookie_t xcb_x_print_print_set_attributes(xcb_connection_t *conn,  
          xcb_x_print_pcontext_t context, uint32_t stringLen, uint8_t pool, uint8_t rule,  
          uint32_t attributes_len, const xcb_x_print_string8_t *attributes);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>context</i>	TODO: NOT YET DOCUMENTED.
<i>stringLen</i>	TODO: NOT YET DOCUMENTED.
<i>pool</i>	TODO: NOT YET DOCUMENTED.
<i>rule</i>	TODO: NOT YET DOCUMENTED.
<i>attributes_len</i>	TODO: NOT YET DOCUMENTED.
<i>attributes</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_x_print_print_set_attributes_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from xprint.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.