

NAME

`xcb_x_print_print_set_image_resolution` -

SYNOPSIS

```
#include <xcb/xprint.h>
```

Request function

```
xcb_x_print_print_set_image_resolution_cookie_t
xcb_x_print_print_set_image_resolution(xcb_connection_t *conn,
xcb_x_print_pcontext_t context, uint16_t image_resolution);
```

Reply datastructure

```
typedef struct xcb_x_print_print_set_image_resolution_reply_t {
    uint8_t response_type;
    uint8_t status;
    uint16_t sequence;
    uint32_t length;
    uint16_t previous_resolutions;
} xcb_x_print_print_set_image_resolution_reply_t;
```

Reply function

```
xcb_x_print_print_set_image_resolution_reply_t
*xcb_x_print_print_set_image_resolution_reply(xcb_connection_t *conn,
xcb_x_print_print_set_image_resolution_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

context TODO: NOT YET DOCUMENTED.

image_resolution
TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_X_PRINT_PRINT_SET_IMAGE_RESOLUTION*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

status TODO: NOT YET DOCUMENTED.

previous_resolutions

TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_x_print_print_set_image_resolution_cookie_t*. Errors have to be handled when calling the reply function *xcb_x_print_print_set_image_resolution_reply*.

If you want to handle errors in the event loop instead, use

xcb_x_print_print_set_image_resolution_unchecked. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xprint.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.