

NAME

`xcb_xevie_send` -

SYNOPSIS

```
#include <xcb/xevie.h>
```

Request function

```
xcb_xevie_send_cookie_t xcb_xevie_send(xcb_connection_t *conn, xcb_xevie_event_t event,  
uint32_t data_type);
```

Reply datastructure

```
typedef struct xcb_xevie_send_reply_t {  
    uint8_t response_type;  
    uint8_t pad0;  
    uint16_t sequence;  
    uint32_t length;  
    uint8_t pad1[24];  
} xcb_xevie_send_reply_t;
```

Reply function

```
xcb_xevie_send_reply_t *xcb_xevie_send_reply(xcb_connection_t *conn,  
xcb_xevie_send_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

event TODO: NOT YET DOCUMENTED.

data_type TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_XEVIE_SEND*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

DESCRIPTION

RETURN VALUE

Returns an *xcb_xevie_send_cookie_t*. Errors have to be handled when calling the reply function *xcb_xevie_send_reply*.

If you want to handle errors in the event loop instead, use *xcb_xevie_send_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xevie.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.