

NAME

`xcb_xf86dri_create_context` -

SYNOPSIS

```
#include <xcb/xf86dri.h>
```

Request function

```
xcb_xf86dri_create_context_cookie_t xcb_xf86dri_create_context(xcb_connection_t *conn,
    uint32_t screen, uint32_t visual, uint32_t context);
```

Reply datastructure

```
typedef struct xcb_xf86dri_create_context_reply_t {
    uint8_t response_type;
    uint8_t pad0;
    uint16_t sequence;
    uint32_t length;
    uint32_t hw_context;
} xcb_xf86dri_create_context_reply_t;
```

Reply function

```
xcb_xf86dri_create_context_reply_t *xcb_xf86dri_create_context_reply(xcb_connection_t *conn,
    xcb_xf86dri_create_context_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

| | |
|----------------|----------------------------|
| <i>conn</i> | The XCB connection to X11. |
| <i>screen</i> | TODO: NOT YET DOCUMENTED. |
| <i>visual</i> | TODO: NOT YET DOCUMENTED. |
| <i>context</i> | TODO: NOT YET DOCUMENTED. |

REPLY FIELDS

| | |
|----------------------|--|
| <i>response_type</i> | The type of this reply, in this case <code>XCB_XF86DRI_CREATE_CONTEXT</code> . This field is also present in the <code>xcb_generic_reply_t</code> and can be used to tell replies apart from each other. |
| <i>sequence</i> | The sequence number of the last request processed by the X11 server. |

length The length of the reply, in words (a word is 4 bytes).

hw_context TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_xf86dri_create_context_cookie_t*. Errors have to be handled when calling the reply function *xcb_xf86dri_create_context_reply*.

If you want to handle errors in the event loop instead, use *xcb_xf86dri_create_context_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xf86dri.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.