

**NAME**

xcb\_xfixes\_set\_gc\_clip\_region -

**SYNOPSIS**

```
#include <xcb/xfixes.h>
```

**Request function**

```
xcb_void_cookie_t xcb_xfixes_set_gc_clip_region(xcb_connection_t *conn, xcb_gcontext_t gc,  
        xcb_xfixes_region_t region, int16_t x_origin, int16_t y_origin);
```

**REQUEST ARGUMENTS**

<i>conn</i>	The XCB connection to X11.
<i>gc</i>	TODO: NOT YET DOCUMENTED.
<i>region</i>	TODO: NOT YET DOCUMENTED.
<i>x_origin</i>	TODO: NOT YET DOCUMENTED.
<i>y_origin</i>	TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_xfixes\_set\_gc\_clip\_region\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from xfixes.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.