

NAME

xcb_xfixes_set_window_shape_region -

SYNOPSIS

```
#include <xcb/xfixes.h>
```

Request function

```
xcb_void_cookie_t xcb_xfixes_set_window_shape_region(xcb_connection_t *conn,  
    xcb_window_t dest, xcb_shape_kind_t dest_kind, int16_t x_offset, int16_t y_offset,  
    xcb_xfixes_region_t region);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>dest</i>	TODO: NOT YET DOCUMENTED.
<i>dest_kind</i>	TODO: NOT YET DOCUMENTED.
<i>x_offset</i>	TODO: NOT YET DOCUMENTED.
<i>y_offset</i>	TODO: NOT YET DOCUMENTED.
<i>region</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_xfixes_set_window_shape_region_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xfixes.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.