

NAME

xcb_xinerama_get_screen_count -

SYNOPSIS

```
#include <xcb/xinerama.h>
```

Request function

```
xcb_xinerama_get_screen_count_cookie_t xcb_xinerama_get_screen_count(xcb_connection_t *conn,  
xcb_window_t window);
```

Reply datastructure

```
typedef struct xcb_xinerama_get_screen_count_reply_t {  
    uint8_t    response_type;  
    uint8_t    screen_count;  
    uint16_t   sequence;  
    uint32_t   length;  
    xcb_window_t window;  
} xcb_xinerama_get_screen_count_reply_t;
```

Reply function

```
xcb_xinerama_get_screen_count_reply_t  
*xcb_xinerama_get_screen_count_reply(xcb_connection_t *conn,  
xcb_xinerama_get_screen_count_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

window TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_XINERAMA_GET_SCREEN_COUNT*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

screen_count TODO: NOT YET DOCUMENTED.

window TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_xinerama_get_screen_count_cookie_t*. Errors have to be handled when calling the reply function *xcb_xinerama_get_screen_count_reply*.

If you want to handle errors in the event loop instead, use *xcb_xinerama_get_screen_count_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from xinerama.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.