

NAME

xcb_xkb_access_x_notify_event_t -

SYNOPSIS

```
#include <xcb/xkb.h>
```

Event datastructure

```
typedef struct xcb_xkb_access_x_notify_event_t {
    uint8_t    response_type;
    uint8_t    xkbType;
    uint16_t   sequence;
    xcb_timestamp_t time;
    uint8_t    deviceID;
    xcb_keycode_t keycode;
    uint16_t   detail;
    uint16_t   slowKeysDelay;
    uint16_t   debounceDelay;
    uint8_t    pad0[16];
} xcb_xkb_access_x_notify_event_t;
```

EVENT FIELDS

response_type The type of this event, in this case *XCB_XKB_ACCESS_X_NOTIFY*. This field is also present in the *xcb_generic_event_t* and can be used to tell events apart from each other.

sequence The sequence number of the last request processed by the X11 server.

xkbType NOT YET DOCUMENTED.

time NOT YET DOCUMENTED.

deviceID NOT YET DOCUMENTED.

keycode NOT YET DOCUMENTED.

detail NOT YET DOCUMENTED.

slowKeysDelay
NOT YET DOCUMENTED.

debounceDelay NOT YET DOCUMENTED.

DESCRIPTION

SEE ALSO

AUTHOR

Generated from xkb.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.