

NAME

xcb_xkb_action_message_event_t -

SYNOPSIS

```
#include <xcb/xkb.h>
```

Event datastructure

```
typedef struct xcb_xkb_action_message_event_t {
    uint8_t      response_type;
    uint8_t      xkbType;
    uint16_t     sequence;
    xcb_timestamp_t time;
    uint8_t      deviceID;
    xcb_keycode_t keycode;
    uint8_t      press;
    uint8_t      keyEventFollows;
    uint8_t      mods;
    uint8_t      group;
    xcb_xkb_string8_t message[8];
    uint8_t      pad0[10];
} xcb_xkb_action_message_event_t;
```

EVENT FIELDS

response_type The type of this event, in this case *XCB_XKB_ACTION_MESSAGE*. This field is also present in the *xcb_generic_event_t* and can be used to tell events apart from each other.

sequence The sequence number of the last request processed by the X11 server.

xkbType NOT YET DOCUMENTED.

time NOT YET DOCUMENTED.

deviceID NOT YET DOCUMENTED.

keycode NOT YET DOCUMENTED.

press NOT YET DOCUMENTED.

keyEventFollows

NOT YET DOCUMENTED.

mods

NOT YET DOCUMENTED.

group

NOT YET DOCUMENTED.

message

NOT YET DOCUMENTED.

DESCRIPTION

SEE ALSO

AUTHOR

Generated from xkb.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.