NAME

    xcb_xkb_get_kbd_by_name -

SYNOPSIS

    #include <xcb/xkb.h>

  Request function

    xcb_xkb_get_kbd_by_name_cookie_t **xcb_xkb_get_kbd_by_name**(xcb_connection_t *_conn_,
        xcb_xkb_device_spec_t _deviceSpec_, uint16_t _need_, uint16_t _want_, uint8_t _load_);

  Reply datastructure

    typedef struct xcb_xkb_get_kbd_by_name_reply_t {
      uint8_t   _response_type_;
      uint8_t   _deviceID_;
      uint16_t   _sequence_;
      uint32_t   _length_;
      xcb_keycode_t _minKeyCode_;
      xcb_keycode_t _maxKeyCode_;
      uint8_t   _loaded_;
      uint8_t   _newKeyboard_;
      uint16_t   _found_;
      uint16_t   _reported_;
      uint8_t   _pad0_[16];
    } **xcb_xkb_get_kbd_by_name_reply_t**;

  Reply function

    xcb_xkb_get_kbd_by_name_reply_t ***xcb_xkb_get_kbd_by_name_reply**(xcb_connection_t *_conn_,
        xcb_xkb_get_kbd_by_name_cookie_t _cookie_, xcb_generic_error_t **_e_);

  Reply accessors

    xcb_xkb_get_kbd_by_name_replies_t *xcb_xkb_get_kbd_by_name_replies (const
    xcb_xkb_get_kbd_by_name_request_t *reply)

REQUEST ARGUMENTS

    conn   The XCB connection to X11.

    deviceSpec   TODO: NOT YET DOCUMENTED.

    need   TODO: NOT YET DOCUMENTED.

want   TODO: NOT YET DOCUMENTED.

load   TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type   The type of this reply, in this case *XCB_XKB_GET_KBD_BY_NAME*. This field is
                  also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each
                  other.

sequence   The sequence number of the last request processed by the X11 server.

length   The length of the reply, in words (a word is 4 bytes).

deviceID   TODO: NOT YET DOCUMENTED.

minKeyCode   TODO: NOT YET DOCUMENTED.

maxKeyCode   TODO: NOT YET DOCUMENTED.

loaded   TODO: NOT YET DOCUMENTED.

newKeyboard   TODO: NOT YET DOCUMENTED.

found   TODO: NOT YET DOCUMENTED.

reported   TODO: NOT YET DOCUMENTED.

DESCRIPTION
RETURN VALUE

Returns an *xcb_xkb_get_kbd_by_name_cookie_t*. Errors have to be handled when calling the reply
function *xcb_xkb_get_kbd_by_name_reply*.

If you want to handle errors in the event loop instead, use *xcb_xkb_get_kbd_by_name_unchecked*. See
xcb-requests(3) for details.

ERRORS

This request does never generate any errors.

SEE ALSO
AUTHOR

Generated from xkb.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.