

NAME

xcb_xkb_set_compat_map -

SYNOPSIS

```
#include <xcb/xkb.h>
```

Request function

```
xcb_void_cookie_t xcb_xkb_set_compat_map(xcb_connection_t *conn,  
    xcb_xkb_device_spec_t deviceSpec, uint8_t recomputeActions, uint8_t truncateSI, uint8_t groups,  
    uint16_t firstSI, uint16_t nSI, const xcb_xkb_sym_interpret_t *si, const  
    xcb_xkb_mod_def_t *groupMaps);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>deviceSpec</i>	TODO: NOT YET DOCUMENTED.
<i>recomputeActions</i>	TODO: NOT YET DOCUMENTED.
<i>truncateSI</i>	TODO: NOT YET DOCUMENTED.
<i>groups</i>	TODO: NOT YET DOCUMENTED.
<i>firstSI</i>	TODO: NOT YET DOCUMENTED.
<i>nSI</i>	TODO: NOT YET DOCUMENTED.
<i>si</i>	TODO: NOT YET DOCUMENTED.
<i>groupMaps</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_xkb_set_compat_map_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from xkb.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.