

**NAME**

**xo\_set\_style**, **xo\_set\_style\_name** - set the output style for a libxo handle

**LIBRARY**

Text, XML, JSON, and HTML Output Emission Library (libxo, -lxo)

**SYNOPSIS**

```
#include <libxo/xo.h>
```

*void*

```
xo_set_style(xo_handle_t *handle, unsigned style);
```

*int*

```
xo_set_style_name(xo_handle_t *handle, const char *style);
```

**DESCRIPTION**

Use the **xo\_set\_style()** function to set the output style for a handle. To use the default handle, pass a NULL handle. The set of output styles used by **libxo** is:

Flag	Description
XO_STYLE_TEXT	Traditional text output
XO_STYLE_XML	XML encoded data
XO_STYLE_JSON	JSON encoded data
XO_STYLE_HTML	HTML encoded data

The **xo\_set\_style\_name()** function can be used to set the style based on a name encoded as a string. The name can be any of the styles: "text", "xml", "json", or "html".

**EXAMPLE:**

```
xo_set_style_name(NULL, "html");
```

**SEE ALSO**

xo\_emit(3), libxo(3)

**HISTORY**

The **libxo** library first appeared in FreeBSD 11.0.

**AUTHORS**

**libxo** was written by Phil Shafer <phil@freebsd.org>.