

NAME

zip_file_set_external_attributes - set external attributes for file in zip

LIBRARY

libzip (-lzip)

SYNOPSIS

```
#include <zip.h>
```

int

```
zip_file_set_external_attributes(zip_t *archive, zip_uint64_t index, zip_flags_t flags, zip_uint8_t opsys,  
zip_uint32_t attributes);
```

DESCRIPTION

The **zip_file_set_external_attributes()** function sets the operating system and external attributes for the file at position *index* in the zip archive. Currently, no *flags* are supported.

For a list of known *opsys* values, see *zip_file_get_external_attributes(3)*.

RETURN VALUES

Upon successful completion 0 is returned. Otherwise, -1 is returned and the error information in *archive* is set to indicate the error.

ERRORS

zip_file_set_external_attributes() fails if:

[ZIP_ER_INVAL] *index* is not a valid file index in *archive*.

[ZIP_ER_MEMORY]

Required memory could not be allocated.

[ZIP_ER_RDONLY]

The *archive* was opened in read-only mode.

SEE ALSO

libzip(3), *zip_file_get_external_attributes(3)*

HISTORY

zip_file_set_external_attributes() was added in libzip 0.11.2.

AUTHORS

Dieter Baron <dillo@nih.at> and Thomas Klausner <tk@giga.or.at>