

NAME

zip_set_archive_flag - set zip archive flag

LIBRARY

libzip (-lzip)

SYNOPSIS

```
#include <zip.h>
```

int

```
zip_set_archive_flag(zip_t *archive, zip_flags_t flag, int value);
```

DESCRIPTION

The **zip_set_archive_flag()** function sets the flag *flag* for the archive *archive* to the value *value*.

Supported flags are:

ZIP_AFL_CREATE_OR_KEEP_FILE_FOR_EMPTY_ARCHIVE

If this flag is cleared, the archive file will be removed if the archive is empty. If it is set, an empty archive will be created, which is not recommended by the zip specification.

ZIP_AFL_WANT_TORRENTZIP

If this flag is set, the archive will be written in torrentzip format.

RETURN VALUES

Upon successful completion 0 is returned, and -1 if an error occurred.

SEE ALSO

libzip(3), zip_get_archive_flag(3)

HISTORY

zip_set_archive_flag() was added in libzip 0.9. In libzip 0.11 the type of *flag* was changed from *int* to *zip_flags_t*. ZIP_AFL_CREATE_OR_KEEP_FILE_FOR_EMPTY_ARCHIVE and ZIP_AFL_WANT_TORRENTZIP were added in libzip 1.10.0.

AUTHORS

Dieter Baron <dillo@nih.at> and Thomas Klausner <tk@giga.or.at>